

## FEATURES

- Standalone version with Magnetic & Screw base
- Focusable 8° to 55°
- Fully dimmable with onboard dimmer

## 6W ACCESSORIES



**L-MTAS-20**  
ANGLED  
SNOOT



**L-MTBD-20**  
BARNDOOR




**L-MTFH-20**  
FILTER HOLDER



**TECHNICAL DATA**

<b>Voltage</b>	DC 11V-24V	<b>Color Finishing</b>	Black, White and Silver
<b>Led Wattage</b>	6W	<b>Working Temperature</b>	recommended 10°C to 25°C
<b>Wattage Once Used</b>	7.2W	<b>Storage Temperature</b>	recommended 22°C
<b>Input Current</b>	650mA - 330mA	<b>Certificates &amp; Warranty</b>	UL - CE / 5 years
<b>Beam Angles</b>	Zoomable 8° to 55°	<b>Drivers Compatible</b>	CV
<b>Pan / Tilt</b>	355°/90°	<b>Lifespan</b>	50000 hours
<b>Luminous Flux &amp; Lumens</b>	813lm @RA97 / 255lm	<b>Lens</b>	Glass
<b>Color Temperatures Available</b>	3000K,4000K,5000K	<b>LED</b>	COB
<b>Adapter</b>	Surface mount	<b>Class</b>	⚡
<b>Dimmable Options</b>	On board Dimmer: PWM, range 0-100%	<b>Rating</b>	IP30
<b>CRI</b>	97 typ	<b>Dimensions</b>	112*45*45 (mm)
<b>Weight</b>	226g	<b>Indoor Use</b>	only
<b>Main Material</b>	Aluminum	<b>Length of Tail</b>	145cm

**PHOTOMETRICS**



**DRIVERS**

Driver	Watts/Driver	80% Capacity	# Fixtures/Driver*	Current
LPV-100-12	100W	80W	10 Fixtures	CV
LPV-60-12	60W	48W	6 Fixtures	CV
LPV-35-12	35W	28W	3 Fixtures	CV
NPF-90-12	90W	72W	8 Fixtures	CV & CC
NPF-40-12	40W	32W	4 Fixtures	CV & CC

**VARIATIONS**



**L-MTSP-22**  
L-MTSP-22 with onboard dimmer



**L-MTFS-22**  
6W Quadri Framing Shutter

Please check product cut sheets for details - driver indications vary per product.