



SPECIFICATIONS

	Nano/Micro	Micro	Mini	Mini	Mini
Active Diameter	1.5mm	2.0mm	3.0mm	4.0mm	5.0mm
Outside Diameter	2.0mm	2.8mm	6.0mm	7.0mm	8.0mm
Minimum 90o turning radius	20mm	40mm	50mm	60mm	65mm
	(3/4")	(1.57")	(2")	(3")	(4")

RECOMMENDED FIBER TAILS PER BUNDLE

Illuminators	1.5mm fiber Optimal/Max	2.00m fiber Optimal/Max	3.0mm fiber Optimal/Max	4.0mm fiber Optimal/Max	5.0mm fiber Optimal/Max
15-125					
10-200 series					
15-135	40/60	18/24	16/20	10/12	5/7
15-145					

For 80-105 - 10 x 2mm fibers per port - there are 5 ports.

TYPICAL FIBER BUNDLES WITH ORDER CODE:

- **Bundle 1.5 x 24 x 3**
1.5mm x 24 tails x 3 meters, to common connector
- **Bundle 2 x 16 x 3**
2.0mm x 16 tails x 3 meters, to common connector
- **Bundle combo 1.5 x 10 x 3 + 2 x 10 x 3**
Combo - 20 tails, 10 x 1.5mm and 10 x 2 x 3 meters to common connector
- **Bundle 3 x 12 x 4**
3.0mm x 12 tails x 4 meters, to common connector

Fiber active diameter x # tails x length/tail - meters

Example: 2mm x 16 x 3 meters

Custom fiber bundles of any length and combination of diameters available as standard order.

Maximum tail length for optimal performance is recommended to be less than 20'.



MICRO / NANO BUNDLE



**MINI BUNDLE W/
FERRULES**



**COMMON CONNECTOR
FACTORY POLISHED**

