



FEATURES

- Very High output and CRI
- Dims from 100% to black
- 30mm port accepts all Luxam fiber bundles
- No light leak from the case
- Contains multi lens optic array for maximum output and uniformity
- Silent convection cooling

TECHNICAL DATA

Fiber Port	30mm	Expected LED life	40,000 hours						
Input power	90-240V AC 60Hz	Operating temp	+5° <ta<40°C						
Total power consumption	30 watts	Housing	Aluminum powder coated						
Dimming	100% to black local potentiometer	Size	199.5 x 131.7 x 98.5 / 8" x 5.2" x 3.9"						
Cooling	Quiet Synjet cooling module	Weight	1.4kg / 3lbs						
Acoustic rating	22 dB/26 dB	Maximum Tails/ bundle	CAX -1 – 140, CAX2 – 24, CAX3 – 20, CAX4 – 12, CAX5 - 7						
LED luminous flux	<table border="1"> <tr> <td>3000K – 2529 Lm</td> <td>3500K – 2940 Lm</td> <td>4000K – 3007Lm</td> </tr> </table>	3000K – 2529 Lm	3500K – 2940 Lm	4000K – 3007Lm	CRI	<table border="1"> <tr> <td>3000K – 97</td> <td>3500K – 90+</td> <td>4000K – 90+</td> </tr> </table>	3000K – 97	3500K – 90+	4000K – 90+
3000K – 2529 Lm	3500K – 2940 Lm	4000K – 3007Lm							
3000K – 97	3500K – 90+	4000K – 90+							

SAMPLE ORDER CODES

Model	Color	Control
10-200-BP-3K		
10-200-BP-3.5K		
10-200-BP-4K		

Custom LED and configurations available upon request