



FEATURES

- Very High output and CRI
- Dims from 100% to black
- 30mm port accepts all Luxam fiber bundles
- No light leak from the case
- Contains multi lens optic array for maximum output and uniformity
- DMX input/output through Cat 6 connectors
- Silent convection cooling

TECHNICAL DATA

Fiber Port	30mm	Expected LED life	40,000 hours						
Input power	90-240V AC 60Hz	Operating temp	+5° <ta<40°C						
Total power consumption	41 watts	Housing	Aluminum powder coated						
Dimming	100% to black potentiometer /DMX	Size	193.6 x 166.7 x 98.5 / 7.62" x 6.5" x 3.9"						
Cooling	Quiet Synjet cooling module	Weight	1.44kg / 3.2lbs						
Acoustic rating	22 dB/26 dB	Maximum Tails/ bundle	CAX -1 – 140, CAX2 – 24, CAX3 – 20, CAX4 – 12, CAX5 - 7						
LED luminous flux	<table border="1"> <tr> <td>3000K – 3150 Lm</td> <td>3500K – 3550 Lm</td> <td>4000K – 3950Lm</td> </tr> </table>	3000K – 3150 Lm	3500K – 3550 Lm	4000K – 3950Lm	CRI	<table border="1"> <tr> <td>3000K – 97</td> <td>3500K – 90+</td> <td>4000K – 90+</td> </tr> </table>	3000K – 97	3500K – 90+	4000K – 90+
3000K – 3150 Lm	3500K – 3550 Lm	4000K – 3950Lm							
3000K – 97	3500K – 90+	4000K – 90+							

SAMPLE ORDER CODES

Model	Color	Control
10-200-BP-DMX-3K		
10-200-BP-DMX-3.5K		
10-200-BP-DMX-4K		

Custom LED and configurations available upon request