



FEATURES

- Fully focusable 9° to 70°
- Accepts all 1W accessories (barndoor, snoots, angled, snoots)
- Can add a dimmer to the driver
- Magnet base option available
- These fixtures need to be wired together in series.

1W ACCESSORIES



L-MTAS-10
ANGLED SNOOT



L-MTBD-10
BARNDOOR



L-MTFH-10
FILTER HOLDER



L-MTBR-10
BEAM REDUCER



DRIVERS

Driver	Min - Max # Fixtures	Current	Setting
AD-36-200-1200-U1P1	3-18 Fixtures	CC	350mA (10-54V)
SE-10-350-700-W1A	1-4 Fixtures	CC	350mA (2-12V)
SE-12-350-700-W1A	4-8 Fixtures	CC	350mA (10-24V)
SE-20-100-700-W1A1	4-15 Fixtures	CC	350mA (9-42V)
SE-30-200-800-W1A	4-15 fixtures	CC	350mA (9-42V)
SE-40-300-1050-W1A	4-15 Fixtures	CC	350mA (9-42V)
DMX-25-150-900-U1P1	4-18 Fixtures	CC	350mA (10-54V)
L-CT-DMX/RDW-1-3W-6CH	1-6 Fixtures/Channel	CC	350mA (3-21V)

SCREW SIZES Focus and Articulation: 0.9mm
Base: 0.9mm

VARIATIONS



Please check product cut sheets for details - driver indications vary per product.